

REPLACEMENT CHECKS FOR BARRACUDA VALVES

RATINGS: 2 1/2" - 4" 750 P.S.I., 5" - 6" 700 P.S.I. 8" 600 P.S.I., 10" 500 P.S.I., 12" 400 P.S.I. Reducing Couplings 300 P.S.I.

GASKET:

MATERIAL: EPDM Temperature Rating: -30°C to +110°C; -20°F to +230°F. Applications: Water, diluted acids, oil free air, waste, high temperature vapors, etc.

DESIGN: "C" Type Gasket standard design, provides a pressure responsive, leak-tight seal in both pressure and vacuum applications without the aid of external forces.

Ductile cast iron conforming to ASTM A536, Grade 65-45-12 equal to QT 450-12. Surface Finish: Standard dip painted.

Optional fused bonded epoxy coated in various colors. Vacuum applications without the aid of external forces.

REPLACEMENT CHECKS FOR BARRACUDA VALVES

Model Number	Size	Qty. per Carton	Weight per Carton (Lbs.)	List Price (Each)
FRP4.00-SS-CHECK-1ST	2 1/2"-4"	1	2	\$802
FRP4.00-SS-CHECK-2ND	2 1/2"-4"	1	2	\$990
FDC4.00-SS-CHECK-1ST	2 1/2"-4"	1	2	\$802
FDC4.00-SS-CHECK-2ND	2 1/2"-4"	1	2	\$990
FRP8.00-SS-CHECK-1ST	6"-8"	1	4	\$1,788
FRP8.00-SS-CHECK-2ND	6"-8"	1	4	\$1,581
FDC8.00-SS-CHECK-1ST	6"-8"	1	4	\$1,581
FDC8.00-SS-CHECK-2ND	6"-8"	1	4	\$1,581

RUBBER REPAIR KITS FOR BARACUDA VALVES

Model Number	Size	Qty. per Carton	Weight per Carton (Lbs.)	List Price (Each)
FDC-FRP4.0-SS-RUBKIT	2 1/2"-4"	1	1	\$340
FDC-FRP8.0-SS-RUBKIT	6"-8"	1	1	\$641
FRP2-8-SS-RELIEF-KIT	2 1/2"-8"	1	2	\$533
FRP4.00-SS-REL-VLV	2 1/2"-4"	1	2	\$1,931
FRP8.00-SS-REL-VLV	6"-8"	1	2	\$1,931