



Spec Sheet

ISO 9002 Manufacturer- 600 WOG RATED- BRONZE BALL VALVES

- Full Port
- Pressure rated at 600 psi water, Working Temperature:-30°C≤t≤200°C
- Applicable Medium:Water,Oil,Gas,Non-Causticity Liquid Saturated Steam.
- Fast ¼ turn open or close operation
- **Solid**, chrome plated brass ball
- Bottom entry , blow-out proof stem
- Adjustable stem packing gland
- Vinyl insulated heavy duty plated steel handles
- Non-corrosive Stainless Steel nut for handle
- PTFE stem packing and seats
- Freeze Plug (tested by 3rd party), rated at minimum 1500psi burst pressure
- Valve body wall thickness is minimum 2 times that of normal ball valve
- Lead free brass or lead free bronze option available ½, ¾ , 1 , & 2 inch sizes
- *5 year warranty against splitting the side of the valve body
- * warranty void if any other plug is installed in place of OEM Freeze Plug
- All threads are standard NPT on valves and freeze plugs

VALVE SIZE	PLUG SIZE	TOOL SIZE
1/2 INCH	3/8TH	10mm
3/4 inch	1/2 inch	13mm
1 inch	3/4 inch	11/16th
2 inch	1 1/4 inch	1/2in ratchet
4 inch	3 inch	1/2 inch ratchet